

WORK STOCK DIESEL TRUCKS

ENGINE:

- Stock engine only for make, model, and year of truck.
- Diesel fuel only. No propane or water injection.
- Turbo charger must be stock appearing for make of truck. Modifications are permitted but must pass a 2.55" plug test. 6.4 Liter Powerstroke may utilize the factory twin turbos.
- Any engine programmers are permitted.
- Aftermarket air cleaner/intakes are permitted.
- Exhaust must exit behind cab of vehicle and must be pointed upwards. Exhaust must have (2) 3/8 diameter rods/bolts inserted into exhaust in a cross pattern with both rods 90° from each other. Rods/bolts must be as close to the turbo as possible. Tech inspection committee will have final say on location.
- Radiator must have a sufficient overflow reservoir.
- No ice or ice water will be permitted on intercoolers.
- Injection pump is limited to 1 stock appearing pump.
- No velocity stack air intakes.

HITCH:

- Hitch height: 26" maximum.
- Hitch point must have a 3.75" hole minimum.
- Must be a Reese style hitch/receiver. No pulling from bumper.
- Hitch must use hitch pin. Bolts are prohibited.
- Hitch must be stationary in all directions.
- Hitch may be reinforced and supported for strength. No part of the hitch will be permitted forward of the centerline of the rear axle.
- No component of the hitch may be connected or in contact with the rear axle.

CHASSIS:

- Aftermarket or fabricated front bumpers are permitted. Front ballast will be permitted

- No batteries are to be located inside cab of vehicle unless they are in a sealed and covered box.
- Steering system modifications are permitted.
- Traction bars and third links are permitted provided they are bolted. Front of traction bars must have a tether strap to prevent the bar from touching the ground. Suspension must have a minimum of 1" of travel. Air bags or air shocks are prohibited.
- Absolutely no electronic traction control devices.
- Factory spec wheelbase only.
- No more than 5" offset from front wheels to rear.
- Complete factory beds only. Beds and toolboxes must be mounted securely. Any bed without a full floor must be covered.
- DOT tires only. Max 35 x 12.50". No cuts, bars, or siping. Rims may not exceed 12" wide. Aftermarket rims permitted.
- No wheel spacers.
- No tire chains.
- One ton rear axle or less permitted. Dual rear wheels prohibited..
- Fuel cells prohibited.
- Brakes must be fully functional on all 4 corners of the vehicle. No driveline brakes permitted.
- OEM transmission and transfer case only.