

## Half Ton Only Truck Class

Any Questions Call Jeremy Avers or James Davie

1. Any American made truck that is considered ½ ton is permitted that came with a factory 6' or 8' bed. 4-wheel drive trucks may only run 2WD (pull a driveshaft).
2. Tailgates may be welded shut using 3"x¼" strap. A maximum of 48" of strap may be used. The back bumper or tailgate has to be 16" of the ground.
3. No wrapping quarter panels to the bumper. Doors can be welded solid with 3"x3". The driver's door can be skinned.
4. Beds must be welded to the cab of the truck with a 3" strap directly behind the doors.
5. An interior four-point cage is required to compete. The cage may not extend outside of the cab into the bed. However, it may attach vertically to the frame in four locations. No metal may be added to the frame to attach the cage. The vertical bars must be welded directly to the frame.
6. Follow semi stock front bumper rules. Factory bumper brackets can be used or 3"x3" angle or square tubing 10" long.
7. A single piece of 3"x3"x¼" angle iron may be welded from the left front frame rail to the right front frame rail (in front of a-arms) on all front coils sprung trucks only. Front leaf sprung trucks may use a chain from rail to rail or from the engine cradle to each rail.
8. Trucks must securely fasten gas tanks directly behind the center of the cab in the bed. Gas tank protector can be a max 24" off the back of the cab and no wider than frame rails.
9. 48" piece of ¼"x2"x2" angle may be welded on the inside of the tailgate.
10. Fix it plate rule 6"x6"x¼" **follow car rules!** If abused, the plate will be cut off!!!! Can be added to fresh or pre-ran trucks.
11. NO HUMP PLATES
12. **All trucks except factory front leaf spring trucks can run kickers off the front bar to the middle to the A arms no bigger than 2"x2" square tube**
13. Front bumper max height is 24" to the bottom of the bumper.
14. Homemade bumper can be max 8"x 8" x ¼" square tube cannot be loaded. If homemade, you must follow the car rule on the bumper point. Follow Semi Stock front bumper rules.
15. Must run factory leaf springs! Max 5 clamps permitted per side.
16. Trucks with factory front leafs cannot have kicker bars.
17. No bead locks.
18. **Must be at least 20" to the bottom of the rear frame.**
19. **No Smashing bed sides down.**
20. All thread only to lock rear suspension.

21. Absolutely NO front leaf conversions
22. No pointy bumper on rear.
- 23. Lower cradle only for mounting purposes only. May not reinforce the truck in anyway.**
- 24. No bigger than a seven lug rear end**