

Street Stock Gas

ENGINE:

- Maximum displacement of 500 cubic inch, 3% over permitted.
- Pump gasoline only. No racing gasoline, alcohol, ethanol, nitrous oxide, nitro methane or propane allowed.
- OEM cast iron blocks only. Block must be offered in vehicle production per year of vehicle.
- OEM cast iron heads only. OEM aluminum heads allowed only if vehicle was equipped from factory.
- No aluminum intakes unless offered from factory or vehicle is carbureted. No sheet metal intakes.
- Naturally aspirated engines only. Eco-Boost is permitted if OEM stock. No alterations.
- Engine programmers are permitted.
- Single carburetors only. OEM carburetors only. Fuel injection is permitted only if equipped with vehicle from factory. OEM fuel injection only will be allowed. No aftermarket.
- Vehicle must have exhaust system. Exhaust must extend past the rear axle.
- Wet sump engine oil systems only. No dry sumps.
- Radiator must have a sufficient overflow reservoir.

HITCH:

- Hitch height: 20" maximum.
- Hitch point must have a 3.75" hole minimum.
- Must be a Reese style hitch/receiver. No pulling from bumper.
- Hitch must use hitch pin. Bolts are prohibited.
- Hitch must be stationary in all directions..

CHASSIS:

- Factory front bumpers only.
- No batteries are to be located inside cab of vehicle unless they are in a sealed and covered box.
- Factory steering systems only.

- Any weight must be located in the bed behind the cab and securely fastened.
- Plow mounts and brush guards are allowed. Plow pump must be removed. No homemade plow mounts or brush guards. All brackets must include a 3/8" hole in all structural members for inspection.
- Must have full set of functioning head lights.
- Factory suspension only. Helper springs are permitted. No ladder bars or 3rd links.
- Any suspension air bags must contain less than 10 PSI pressure.
- Absolutely no electronic traction control devices.
- Factory spec wheelbase only.
- Complete factory beds only. Beds and toolboxes must be mounted securely. Any bed without a full floor must be covered.
- DOT tires only. Max 35". No cuts, bars, or siping. Any width is permitted. DOT rims only.
- No wheel spacers.
- No tire chains.
- One ton rear axle or less permitted. No dual rear wheels.
- No open drivelines or drop boxes.
- Fuel tanks must remain in the factory location or in the bed behind the cab. Relocated tanks must be SFI approved.
- Brakes must be fully functional on all 4 corners of the vehicle. No driveline brakes permitted.
- OEM transmission and transfer case only.